



Wire Rope



Galvanized and Stainless Steel Aircraft Cable

Improved Plow Steel



Nominal Diameter	Tolerance on Dia.	Approx. Weight	Approx. Weight	Min. Breaking Strength	
				Galvanized	Stainless Steel
inches	inches	kg/1000'	lb/1000'	lb	lb
7 X 7					
1/16	0.010	3.40	7.5	480	480
3/32	0.012	7.26	16.0	920	920
1/8	0.014	12.93	28.5	1,700	1,760
3/16	0.018	28.12	62.0	3,700	3,700
1/4	0.018	48.08	106	6,100	6,100
3/8	0.026	107.05	236	13,300	12,600
7 X 19					
3/32	0.012	7.89	17.4	1,000	920
1/8	0.014	13.15	29.0	2,000	1,760
5/32	0.016	20.41	45.0	2,800	2,400
3/16	0.018	29.48	65.0	4,200	3,700
7/32	0.018	39.01	86.0	5,600	5,000
1/4	0.018	49.90	110.0	7,000	6,400
5/16	0.022	78.47	173.0	9,800	9,000
3/8	0.026	110.22	243.0	14,400	12,000

*Breaking strength listed for comparative purposes. Operating loads may vary, but NEVER exceed the recommended design factor of 20% of the Breaking strength.

