


# Wire Rope




## Galvanized and Stainless Steel Strand



Nominal Diameter	Nominal Diameter of Wires	Approx. Weight	Nominal Breaking Strength
			Extra High Strength
inches	inches	lb/ft	lb
<b>1 X 7</b>			
1/4	0.080	0.121	6,650
5/16	0.109	0.205	11,200
3/8	0.120	0.273	15,400
1/2	0.165	0.517	26,900

Nominal Diameter	Breaking Strength
	lb
<b>1 X 7 Seizing Strand *</b>	
3/32	250
1/8	540

\*Galvanized. Perfect for seizing the ends of wire rope and also for wrapping sling eyes.



Nominal Diameter	Approx. Weight	Approx. Weight	Min. Breaking Strength	
			Galvanized	Stainless Steel
inches	kg/1000'	lg/1000'	lb	lb
<b>1 X 19</b>				
1/8	15.88	35.0	2,100	2,100
3/16	34.93	77.0	4,700	4,700
1/4	61.24	135.0	8,200	8,200
5/16	95.26	210.0	12,500	12,500
3/8	136.08	300.0	18,000	17,500

\*Breaking strength listed for comparative purposes. Operating loads may vary, but NEVER exceed the recommended design factor of 20% of the Breaking strength.

[www.dominionriggingproducts.com](http://www.dominionriggingproducts.com)

