

ASTM80 Standard Link Chain

Proof Coil Chain ASTM80 (G30) • Not Intended For Overhead Lifting



Nominal Size		Working Load Limit (max)		Inside Length (max)		Inside Width (min)	
(in)	mm	kg	lb	mm	inches	mm	inches
1/8	4.00	190	420	22.60	0.89	7.40	0.29
3/16	5.50	360	800	24.10	0.95	10.20	0.40
1/4	7.10	600	1,330	25.40	1.00	12.70	0.50
5/16	8.70	910	2,000	27.90	1.10	12.70	0.50
3/8	10.30	1,270	2,800	31.20	1.23	15.70	0.62
1/2	13.50	2,190	4,800	38.90	1.53	20.30	0.80
5/8	16.70	3,350	7,400	48.30	1.90	25.40	1.00
3/4	19.80	4,700	10,400	54.60	2.15	28.40	1.12
7/8	23.00	6,350	14,000	63.50	2.50	34.80	1.37
1	26.50	8,400	18,600	69.90	2.75	38.10	1.50

Available in Hot Dipped Galvanized, Electro Galvanized, and Self-Colored.

NACM84/90 Standard Link Chain

Proof Coil Chain NACM84/90 (G30) • Not Intended For Overhead Lifting



Nominal Size		Working Load Limit (max)		Inside Length (max)		Inside Width (min)	
(in)	mm	kg	lb	mm	inches	mm	inches
1/8	4.00	170	375	23.9	0.94	6.4	0.25
3/16	5.50	365	800	24.8	0.98	7.7	0.3
1/4	7.00	580	1,300	31.5	1.24	9.8	0.38
5/16	8.00	860	1,900	32.8	1.29	11.2	0.44
3/8	10.00	1,200	2,650	35	1.38	14	0.55
1/2	13.00	2,030	4,500	45.5	1.79	18.2	0.72
5/8	16.00	3,130	6,900	56	2.2	20	0.79
3/4	20.00	4,800	10,600	70	2.76	25	0.98
7/8	22.00	5,810	12,800	77	3.03	27.5	1.03
1	26.00	8,140	17,900	90.9	3.58	31.7	1.25

Available in Hot Dipped Galvanized, Electro Galvanized, and Self-Colored.