

ASTM80 Standard Link Chain

High Test Chain ASTM80 (G43) • Not Intended For Overhead Lifting



Nominal Size		Working Load Limit (max)		Inside Length (max)		Inside Width (min)	
(in)	mm	kg	lb	mm	inches	mm	inches
1/4	7.1	1,180	2,600	21.8	0.86	10.2	0.4
5/16	8.7	1,770	3,900	26.7	1.05	12.2	0.48
3/8	10.3	2,450	5,400	30.3	1.19	14.7	0.58
1/2	13.5	4,170	9,200	36	1.43	19.1	0.75

Available in Hot Dipped Galvanized, Electro Galvanized, and Self-Colored.

NACM84/90 Standard Link Chain

High Test Chain NACM84/90 (G43) • Not Intended For Overhead Lifting



Nominal Size		Working Load Limit (max)		Weight Per 100		Inside Length (max)		Inside Width (min)	
(in)	mm	kg	lb	kg	lb	mm	inches	mm	inches
1/4	7.00	1,180	2,600	30	66.1	31.5	1.24	9.8	0.38
5/16	8.00	1,770	3,900	39	86	32.8	1.29	11.2	0.44
3/8	10.00	2,450	5,400	67.3	148	35	1.38	14	0.55
1/2	13.00	4,170	9,200	110	242	45.5	1.79	18.2	0.72

Available in Hot Dipped Galvanized, Electro Galvanized, and Self-Colored.