

Hay Forks Pulley

Sheave Dia (in)	WLL (tons)	Weight (lbs)	Std Rope Size (in)
4	1	6.38	1 1/4 MR
4	1	6.29	1/2 WR
6	2	14.63	1 1/2 MR
6	2	13.42	5/8 WR



Electro Galvanized

Manila Snatch Block

Sheave Dia (in)	WLL (tons)	Weight (lbs)	End Fitting
6	1200	9.02	Eye
6	1200	9.57	Hook
8	2400	13.20	Eye
8	2400	14.30	Hook
10	4800	26.40	Eye
10	4800	28.60	Hook
12	9600	52.80	Eye
12	9600	57.20	Hook



Electro Galvanized

Try Net Block

Sheave Dia (in)	WLL (tons)	Weight (lbs)	Sheave Dimensions (in)	
			Outside Dia	Rim Thickness
6	5	23.13	6	2 - 3/4
8	10	57.2	8	2 - 7/8



Electro Galvanized

Trawl Block

Sheave Dia (in)	WLL (tons)	Weight (lbs)	Sheave Dimensions (in)	
			Outside Dia	Rim Thickness
8	10	60.72	8	3.75
12	10	90.2	12	3.75
16	20	139.7	16	3.75



Electro Galvanized

