



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 3 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C
- Magnaflux crack detection is performed 100% on each batch.
- Built with ball bearing and enables full swivel feature under load.



8-P025T
For trigger

G-100 Swivel Self Locking Hook

with Ball Bearing, which performs full swivel under load.

Item No.	For Grade 100 Chain			Dimensions (inch)						N.W. lbs
	inch	lbs*	tonnes*	A	D	H	K	P	T	
X-027N-06	7/32	3,200	1.4	0.87	0.47	0.87	5.87	1.10	0.59	1.3
X-027N-07	1/4-5/16	5,700	2.5	1.14	0.51	1.02	7.32	1.34	0.79	2.6
X-027N-10	3/8	8,800	4.0	1.34	0.63	1.34	8.58	1.73	1.02	4.4
X-027N-13	1/2	15,000	6.7	1.69	0.83	1.65	10.87	2.01	1.18	9.0
X-027N-16	5/8	22,600	10.0	1.97	0.91	2.20	12.95	2.36	1.42	15.0
X-027N-20	3/4	35,300	16.0	3.23	0.98	2.56	15.24	2.76	2.09	27.8
X-027N-22	7/8	42,700	19.0	3.74	1.30	2.80	17.99	3.15	1.93	39.6
X-027N-26	1	59,700	26.5	4.53	2.01	3.11	21.06	3.90	2.20	69.3

★ Design factor 4:1 proof tested and certified.