



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 2 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C
- Magnaflux crack detection is performed 100% on each batch.



X-P026
For load pin replacement



8-P044
For latch replacement

G-100 Clevis Sling Hook

with Latch

Item No.	Working Load Limit		For Grade 100 Chain	Dimensions (inch)						N.W.
	lbs*	tonnes*		A	H	K	P1	T	T	
X-043/S-06	3,200	1.4	7/32	0.24	0.91	3.82	0.91	0.59	0.67	0.7
X-043/S-07	5,700	2.5	1/4-5/16	0.35	0.87	3.86	1.06	0.71	0.79	1.1
X-043/S-10	8,800	4.0	3/8	0.43	1.18	4.80	1.34	0.94	0.91	2.2
X-043/S-13	15,000	6.7	1/2	0.55	1.46	5.79	1.73	1.18	1.06	4.0
X-043/S-16	22,600	10.0	5/8	0.67	1.65	6.54	1.89	1.54	1.26	6.8
X-043/S-20	35,300	16.0	3/4	0.94	2.52	8.15	2.24	1.89	1.89	16.0
X-043/S-22	7/8	42,700	19.0	2.01	1.22	2.48	9.65	2.99	2.05	20.5

★ Design factor 4:1 proof tested and certified.