



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with DIN 5692, EN 1677-1 and ASTM A952/A 952M.
- Certified by DGUV GS-MO-15-05.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C
- Not for use with Omega Link
- Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

## G-100 Eye Grab Hook

Item No.	For Grade 100 Chain	WLL tonnes*	Dimensions (mm)					N.W. kg
	mm		A	F	G	K	P	
X-041-06	6	1.4	13	26	8	50	8	0.2
X-041-07	7,8	2.5	16	30	9	62	10	0.3
X-041-10	10	4.0	20	40	13	82	13	0.6
X-041-13	13	6.7	26	52	16	107	17	1.4
X-041-16	16	10.0	30	57	20	132	21	2.4
X-041-20	20	16.0	40	73	24	147	23	4.0
X-041-22	22	19.0	42	70	26	164	26	5.0
X-041-26	26	26.5	50	100	32	207	33	10.1

★ Design factor 4:1 proof tested and certified.