






Kind of attachment																	
Number of legs		1	2	1	2	2	2	2	2	3-4	3-4	3-4	3-4	3-4	3-4	3-4	3-4
Load direction		0°	0°	90°	90°	0-45°	45° - 60°	unsymm.	unsymm.	0 - 45°	45° - 60°	unsymm.	unsymm.	0 - 45°	45° - 60°	unsymm.	unsymm.
Item No.	Thread	WLL(t)															
8-291K-003	M 8	1	2	0.3	0.6	0.42	0.3	0.3	0.3	0.63	0.45	0.3	0.3	0.63	0.45	0.3	0.3
8-291K-004	M10	1	2	0.4	0.8	0.56	0.4	0.4	0.4	0.8	0.6	0.4	0.4	0.8	0.6	0.4	0.4
8-291K-007	M12	2	4	0.75	1.5	1	0.75	0.75	0.75	1.5	1.1	0.75	0.75	1.5	1.1	0.75	0.75
8-291K-015	M16	4	8	1.5	3	2.1	1.5	1.5	1.5	3.1	2.2	1.5	1.5	3.1	2.2	1.5	1.5
8-291K-023	M20	6	12	2.3	4.6	3.2	2.3	2.3	2.3	4.8	3.4	2.3	2.3	4.8	3.4	2.3	2.3
8-291K-032	M24	8	16	3.2	6.4	4.5	3.2	3.2	3.2	6.7	4.8	3.2	3.2	6.7	4.8	3.2	3.2
8-291K-045	M30	12	24	4.5	9	6.3	4.5	4.5	4.5	9.4	6.7	4.5	4.5	9.4	6.7	4.5	4.5
8-291K-070	M36	16	32	7	14	9.8	7	7	7	14.7	10.5	7	7	14.7	10.5	7	7
8-291K-090	M42	24	48	9	18	12.6	9	9	9	18.9	13.5	9	9	18.9	13.5	9	9
8-291K-120	M48	32	64	12	24	16.8	12	12	12	25	18	12	12	25	18	12	12
8-291K-140	M56	34	68	+16	32	22.4	+16	+16	+16	32	24	16	+16	32	24	16	+16
8-291K-150	M64	36	72	++18	36	25.2	++18	++18	++18	36	27	18	++18	36	27	18	++18

+ WLL=16 (was 12)
++ WLL=18 (was 12)