

Extra width inside
allows better works
on large crane hooks.



Type Approval

Oblong Master Link, Code "MF".

Connected to Chain with "YA" connecting link.


Item No.	Trade Size	For Grade 80 Chain(inch)		Working Load Limit		Dimensions (inch)			N.W.
		inch	1-Leg	2-Leg	lbs*	tonnes*	D	IL	
8-003-06 ※	3/8	7/32	--	3,000	1.25	0.43	3.94	2.36	0.4
8-003-0806 ※	1/2	1/4-5/16	7/32	4,920	2.5	0.55	4.72	2.76	0.9
8-003-1008 ※	5/8	3/8	1/4-5/16	6,600	4.0	0.67	5.51	3.15	1.5
8-003-13 ※	3/4	1/2	--	10,320	5.4	0.75	5.91	3.54	2.4
8-003-1310 ※	7/8	1/2	3/8	14,040	7.5	0.87	6.30	3.74	3.3
8-003-16 ※	1	5/8	--	24,360	10.0	0.98	7.48	4.33	4.9
8-003-1613 ※	1-1/8	5/8	1/2	27,000	10.0	1.10	7.09	4.13	6.2
8-003-19 ※	1-1/4	3/4	--	35,160	12.0	1.18	7.87	4.72	8.4
8-003-2216 ※	1-3/8	7/8	5/8	42,000	17.0	1.34	9.45	5.51	12.1
8-003-26 ※	1-1/2	1	--	47,880	25.0	1.50	9.84	5.91	15.4
8-003-2619 ※	1-5/8	1	3/4	60,600	28.0	1.57	9.84	5.91	17.6
8-003-3222 ※	1-3/4	1-1/4	7/8	62,520	37.0	1.77	11.81	7.09	28.0

※ Forged Oblong Master Links.

Design factor 4:1 proof tested and certified Tested acc. to EN 1677

Oblong Master Link with Flat. Code "MFF"

Connected to Chain with "YO" Omega Link.



Item No.	Trade Size	For Grade 80 Chain(inch)		Working Load Limit		Dimensions (inch)			N.W.
		inch	1-Leg	2-Leg	lbs*	tonnes*	D	IL	
8-003F-06 ※	3/8	7/32	--	3,000	1.25	0.43	3.94	2.36	0.4
8-003F-0806 ※	1/2	1/4-5/16	7/32	4,920	2.5	0.55	4.72	2.76	0.9
8-003F-1008 ※	5/8	3/8	1/4-5/16	6,600	4.0	0.67	5.51	3.15	1.5
8-003F-1310 ※	7/8	1/2	3/8	14,040	7.5	0.87	6.30	3.74	3.3
8-003F-1613 ※	1-1/8	5/8	1/2	27,000	10.0	1.10	7.09	4.13	5.9
8-003F-2216 ※	1-3/8	3/4	5/8	42,000	17.0	1.34	9.45	5.51	12.1
8-003F-2619 ※	1-5/8	1	3/4	60,600	28.0	1.57	9.84	5.91	17.4

※ Forged Oblong Master Links.

★ Design factor 4:1 Proof tested and certified

WLL=Working Load Limit Tested acc. to EN 1677