


Clevis Swivel Self Locking Hook. Code " KP "

with Ball Bearing, which performs full swivel under load




Item No.	Working Load Limit		For Grade 80 Chain	Dimensions (inch)						N.W.
	lbs*	tonnes*	inch	A	H	K	P	T		lbs
8-022-06	2,500	1.12	7/32	0.24	0.75	6.14	1.14	0.59		1.8
8-022-07	4,500	2.0	1/4-5/16	0.35	0.94	7.40	1.34	0.79		2.9
8-022-10	7,100	3.15	3/8	0.43	1.19	8.46	1.77	1.02		4.9
8-022-13	12,000	5.3	1/2	0.55	1.57	10.83	2.13	1.19		9.9
8-022-16	18,100	8.0	5/8	0.71	1.93	12.72	2.44	1.42		17.4
8-022-20	28,300	12.5	3/4	0.83	2.36	16.45	3.54	1.91		27.6

★ Design factor 4:1 proof tested and certified
Tested acc. to EN 1677

Eye Swivel Hook. Code " YSW "

with Brass Bushing



Item No.	Working Load Limit		For Grade 80 Chain	Dimensions (inch)								N.W.
	lbs*	tonnes*	inch	A	B	D	H	K	P	T		lbs
8-049-06	2,500	1.12	7/32	1.26	0.88	0.44	0.74	5.35	0.94	0.64		1.3
8-049-07	4,500	2.0	1/4-5/16	1.42	1.06	0.51	0.87	6.10	1.02	0.71		1.9
8-049-10	7,100	3.15	3/8	1.63	1.46	0.62	1.14	7.44	1.42	0.91		3.5
8-049-13	12,000	5.3	1/2	1.81	1.57	0.83	1.38	9.17	1.65	1.10		7.1
8-049-16	18,100	8.0	5/8	2.36	1.97	0.91	1.73	11.02	1.97	1.38		11.7
8-049-20	28,300	12.5	3/4	2.91	3.23	1.02	2.56	14.00	2.20	1.91		20.3


★ Design factor 4:1 proof tested and certified
Tested acc. to EN 1677

⚠ **WARNING INFORMATION:** This hook is a positioning device and is not intended to rotate under load. For swivel hooks designed to rotate under load, see p.130 8-049N.



Eye Swivel Hook. Code "YSWN "

with Ball Bearing, which performs full swivel under load



Item No.	Working Load Limit		For Grade 80 Chain	Dimensions (inch)								N.W.
	lbs*	tonnes*	inch	A	B	D	H	K	P	T		lbs
8-049N-06	2,500	1.12	7/32	1.26	0.88	0.44	0.74	5.35	0.94	0.64		1.3
8-049N-07	4,500	2.0	1/4-5/16	1.42	1.06	0.51	0.87	6.10	1.02	0.71		2.0
8-049N-10	7,100	3.15	3/8	1.63	1.46	0.62	1.14	7.44	1.42	0.91		3.5
8-049N-13	12,000	5.3	1/2	1.81	1.57	0.83	1.38	9.17	1.65	1.10		7.5
8-049N-16	18,100	8.0	5/8	2.36	1.97	0.91	1.73	11.02	1.97	1.38		11.7
8-049N-20	28,300	12.5	3/4	2.91	3.23	1.02	2.56	14.00	2.20	1.91		20.5

★ Design factor 4:1 proof tested and certified
Tested acc. to EN 1677