



- Pivots 180° side loading allowed.
- Manufactured from forged alloy steel, quenched and tempered.
- Manufactured and tested in accordance with EN1677-1.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts are traceable to Test Certification.
- Supplied without bolts; usage of Grade 10.9 or Grade 12.9 bolts is recommended.
- Individually proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.

Bolt-on Tie Down. Code“DAB”.

Designed with spring, stop at any angle supplied without bolt (Metric Thread8-058)

Item No.	Working Load Limit	Dimensions (mm)									N.W.
	tonnes	A	B	D	F	H	K	L	N	R	kg
8-058-1T	1.0	50	72	14	27	55	98	139	14	24	0.7
8-058-3T	3.0	58	84	17	33	50	114	144	18	29	1.1
8-058-5T	5.0	64	116	22	43	74	160	203	23	33	2.5

* Design factor 5:1

* Bolts of grade 10.9 & 12.9 are recommended

Bolt-on Tie Down. Code“DAB”.

Designed with spring, stop at any angle supplied without bolt (UNC Thread 8-058)

Item No.	Working Load Limit	Dimensions (inch)									N.W.
	lbs	A	B	D	F	H	K	L	N	R	lbs
8-058-1T	2200	1.97	2.83	0.55	1.06	2.17	3.86	5.47	0.55	0.94	1.5
8-058-3T	6600	2.28	3.31	0.67	1.30	1.97	4.49	5.67	0.71	1.14	2.4
8-058-5T	11000	2.52	4.57	0.87	1.69	2.91	6.30	7.99	0.91	1.30	5.5

* Design factor 5:1

* Bolts of grade 10.9 & 12.9 are recommended