


## Oblong Master Link, Code "MF".

Connected to Chain with "YA" connecting link.



Extra width inside  
allows better works  
on large crane hooks.



Type Approval


| Item No.   |   | WLL<br>β 0-45°<br>tonnes* | For<br>Grade 80<br>Chain(mm) |        | Dimensions (mm) |     |     | N.W.<br>kg |
|------------|---|---------------------------|------------------------------|--------|-----------------|-----|-----|------------|
|            |   |                           | 1 Leg                        | 2 Leg  | D               | IL  | IW  |            |
| 8-003-06   | ※ | 1.25                      | 6                            | --     | 11              | 100 | 60  | 0.2        |
| 8-003-0806 | ※ | 2.5                       | 7, 8                         | 6      | 14              | 120 | 70  | 0.4        |
| 8-003-1008 | ※ | 4.0                       | 10                           | 7, 8   | 17              | 140 | 80  | 0.7        |
| 8-003-13   | ※ | 5.4                       | 13                           | --     | 19              | 150 | 90  | 1.1        |
| 8-003-1310 | ※ | 7.5                       | 13                           | 10     | 22              | 160 | 95  | 1.5        |
| 8-003-16   | ※ | 10.0                      | 16                           | --     | 25              | 190 | 110 | 2.2        |
| 8-003-1613 | ※ | 10.0                      | 16                           | 13     | 28              | 180 | 105 | 2.8        |
| 8-003-19   | ※ | 12.0                      | 19, 20                       | --     | 30              | 200 | 120 | 3.8        |
| 8-003-2216 | ※ | 17.0                      | 22                           | 16     | 34              | 240 | 140 | 5.5        |
| 8-003-26   | ※ | 25.0                      | 26                           | --     | 38              | 250 | 150 | 7.0        |
| 8-003-2619 | ※ | 28.0                      | 26                           | 19, 20 | 40              | 250 | 150 | 8.0        |
| 8-003-3222 | ※ | 37.0                      | 32                           | 22     | 45              | 300 | 180 | 12.7       |

※ Forged Oblong Master Links.

Design factor 4:1 proof tested and certified Tested acc. to EN 1677

## Oblong Master Link with Flat. Code "MFF"

Connected to Chain with "YO" Omega Link.



| Item No.    |   | WLL<br>β 0-45°<br>tonnes* | For<br>Grade 80<br>Chain(mm) |        | Dimensions (mm) |     |     | N.W.<br>kg |
|-------------|---|---------------------------|------------------------------|--------|-----------------|-----|-----|------------|
|             |   |                           | 1 Leg                        | 2 Leg  | D               | IL  | IW  |            |
| 8-003F-06   | ※ | 1.25                      | 6                            | --     | 11              | 100 | 60  | 0.2        |
| 8-003F-0806 | ※ | 2.5                       | 7, 8                         | 6      | 14              | 120 | 70  | 0.4        |
| 8-003F-1008 | ※ | 4.0                       | 10                           | 7, 8   | 17              | 141 | 80  | 0.7        |
| 8-003F-1310 | ※ | 7.5                       | 13                           | 10     | 23              | 163 | 95  | 1.5        |
| 8-003F-1613 | ※ | 10.0                      | 16                           | 13     | 29              | 180 | 105 | 2.8        |
| 8-003F-2216 | ※ | 17.0                      | 20                           | 16     | 34              | 245 | 140 | 5.3        |
| 8-003F-2619 | ※ | 25.0                      | --                           | 19, 20 | 40              | 257 | 150 | 8.0        |

※ Forged Oblong Master Links.

★ Design factor 4:1 Proof tested and certified

WLL=Working Load Limit Tested acc. to EN 1677