





- Designed specifically for ROV application.
- Forged Steel, Quenched & Tempered, with alloy pins.
- Handles are Carbon Steel.
- Individually stamped with the safe working load.
- Shackle Bows are painted yellow to ensure ease of sight in water.
- Convertible handles on ROV shackle bolts

ROV Anchor Shackle

with Fishtail-handle and Safety Pin
(ROV: Remote Operate Vehicle)

Item No.	Nominal Size	Working Load Limit tonnes	Ultimate Breaking Force tonnes	Dimensions (inch)									N.W. lbs
	in.			A	B	C	D	E	G	H	I	J	
8-941-22	7/8	6.5	32.5	0.9	1.0	2.1	0.8	1.5	2.3	5.8	16.5	4.0	9.3
8-941-26	1	8.5	42.5	1.0	1.1	2.4	0.9	1.7	2.7	6.5	16.9	4.7	10.6
8-941-28	1-1/8	9.5	47.5	1.1	1.3	2.7	1.1	1.8	2.9	7.5	17.9	5.1	12.5
8-941-32	1-1/4	12.0	60.0	1.3	1.4	3.0	1.2	2.1	3.3	8.3	18.4	5.8	15.8
8-941-36	1-3/8	13.5	67.5	1.4	1.5	3.3	1.3	2.3	3.6	9.1	18.8	6.5	18.9
8-941-38	1-1/2	17.0	85.0	1.5	1.8	3.6	1.4	2.4	3.8	10.0	19.3	6.9	23.5
8-941-45	1-3/4	25.0	125.0	1.8	2.0	4.2	1.7	2.9	5.0	12.3	21.1	8.7	38.7
8-941-50	2	35.0	175.0	2.0	2.2	4.8	2.0	3.3	5.7	13.7	22.0	9.8	58.1

* Minimum Ultimate Load is 5 times the Working Load Limit.

Maximun Proof Load is 2 times the Working Load Limit.

Item No.	Nominal Size	Working Load Limit tonnes	Ultimate Breaking Force tonnes	Dimensions (mm)									N.W. kg
	mm			A	B	C	D	E	G	H	I	J	
8-941-22	22	6.5	32.5	22	26	53	21.5	38	58	148	420	102	4.2
8-941-26	26	8.5	42.5	26	28	61	23	44	68	166	429	120	4.8
8-941-28	28	9.5	47.5	28	32	68	27	46	74	190	454	130	5.7
8-941-32	32	12.0	60.0	32	36	76	29.5	54	84	210	467	148	7.2
8-941-36	36	13.5	67.5	36	38	84	32	59	92	232	477	164	8.6
8-941-38	38	17.0	85.0	38	45	92	35	60.5	97	254	489	175	10.7
8-941-45	45	25.0	125.0	45	50	106	44	73	127	313	536	221	17.6
8-941-50	50	35.0	175.0	50	57	122	50.8	83.5	146	347.5	560	247.7	26.4

* Minimum Ultimate Load is 5 times the Working Load Limit.

Maximun Proof Load is 2 times the Working Load Limit.