

- YOKE Swivels are manufactured using the highest grade of material available.
- YOKE Swivels are designed with a safety factor of 5:1.
- YOKE Swivels are available in sizes from 3/4 Tons to 35 Tons.
- YOKE Swivels are available for wire lines 1/4" to 1-1/2".
- YOKE Swivels are zinc plated for corrosion resistance and longer life.
- YOKE Swivels are manufactured with grease fittings for superior performance.
- YOKE Swivels are designed for low starting torque and high rotation speed.
- All Swivels parts are 100% magnaflux crack detected.
- 20,000 cycle fatigue rate to 1.5 times working load limit.
- All parts with batch number for quality certified and traceability.

Angular Contact Bearing Swivels - Eye + Eye

Item No.	Wire Line Size	Working Load Limit	Dimensions (inch)							N.W.
	inch	Tons*	B	I	J	K	L	T	W	lbs
8-306-0075	1/4	0.75	1.30	0.70	0.70	4.10	5.50	0.50	1.50	1.1
8-306-015	3/8	1.50	1.60	0.90	0.90	4.60	6.30	0.60	1.70	2.0
8-306-03	1/2	3	2.00	1.10	1.10	6.20	8.40	0.80	2.00	4.6
8-306-05	5/8	5	2.50	1.30	1.30	8.30	10.90	1.00	2.30	9.7
8-306-085	3/4	8.50	3.00	1.50	1.50	9.80	12.80	1.30	3.20	16.1
8-306-10	7/8	10	4.00	2.10	2.00	12.20	16.30	1.70	3.50	37.4
8-306-15	1	15	4.30	2.50	2.50	12.40	17.40	1.90	4.30	46.3
8-306-25	1 1/4	25	5.20	2.80	2.80	16.00	21.50	2.40	5.10	86.0
8-306-35	1 1/2	35	5.20	2.80	2.80	16.00	21.50	2.40	5.10	101.0

★ Minimum Ultimate Load is 5 times the Working Load Limit.
Maximun Proof Load is 2 times the Working Load Limit.

Item No.	Wire Line Size	Working Load Limit	Dimensions (mm)							N.W.
	mm	Tons*	B	I	J	K	L	T	W	kg
8-306-0075	6	0.75	32	18	19	103	139	12	37	0.5
8-306-015	10	1.50	40	22	23	117	160	15	43	0.9
8-306-03	13	3	51	28	27	158	214	20	51	2.1
8-306-05	16	5	64	33	33	210	276	26	59	4.4
8-306-085	19	8.50	76	38	37	249	325	32	82	7.3
8-306-10	22	10	102	52	44	310	413	42	90	17.0
8-306-15	25	15	108	64	54	316	443	49	110	21.0
8-306-25	32	25	132	70	66	407	547	60	130	39.0
8-306-35	38	35	132	70	66	407	547	60	130	45.8

★ Minimum Ultimate Load is 5 times the Working Load Limit.
Maximun Proof Load is 2 times the Working Load Limit.