





- Rotates through 360° and pivot 180°, and simultaneously allows lifting from any direction.
- Manufactured from forged alloy steel, quenched and tempered.
- Manufactured and tested in accordance with EN1677-1.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolt are Metric thread (ASME / ANSI B18.3.1M).
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.
- Quick and simple assembly, just a tapped hole is required.

» Taiwan Patent
» China Patent



Anchor Point Long Bolt

Metric Thread (8-231)



Item No.	Working Load Limit		Thread version			Dimensions										Torque in Nm	N.W. kg
	y	(z)	M	E	Pitch	A	B	C	D	F	G	H	R	S	SW		
	tonnes		mm	mm	DIN13				mm								
8-231-005/105L	0.5	0.8	M 8	83	1.25	33	42	28	11	80	58	23	17	6	13	30	0.3
8-231-007/125L	0.7	1.2	M 10	103	1.5	33	41	29	11	80	58	23	17	6	17	60	0.4
8-231-010/150L	1.0	2.0	M 12	128	1.75	33	40	31	11	80	58	23	17	8	19	100	0.4
8-231-020/185L	2.0	3.2	M 16	149	2	50	54	46	17	117	90	36	27	10	24	150	1.1
8-231-030/230L	3.0	5.6	M 20	194	2.5	50	52	49	17	117	90	36	27	12	30	250	1.4
8-231-050/265L	5.0	9.2	M 24	221	3	72	81	59	25	163	125	44	37	14	36	400	3.2
8-231-078/340L	7.8	12.0	M 30	278	3.5	87	94	81	30	204	148	62	46	17	46	500	6.3
8-231-125/300L	12.5	14.0	M 36	225	4	110	112	98	36	247	188	75	57	22	55	1000	10.9
8-231-156/350L	15.6	16.0	M 42	268	4.5	110	101	108	36	247	188	83	57	24	65	1500	13.9
8-231-200/385L	20.0	20.0	M 48	303	5	110	97	113	36	248	188	83	57	27	75	2000	14.7

* Proof Load is 2.5 times the Working Load Limit on the 4:1 design factor.
* Bolt in GEOMET® finished on request